

4CH /8CH H.264 Stand-Alone Economic Network DVR



■ Features

- ◆ H.264 standard compression format with efficient processing and clear image
- ◆ Support CIF recording encoding
- ◆ Two high-speed USB2.0 interfaces, you can mix backup and mouse
- ◆ Support six operations at the same time, recording, playback, network transmission, backup, mobile monitoring, PTZ control etc
- ◆ Support IE and client, remote parameter settings / convenient remote network access function without need to apply for any domain names, plug and play
- ◆ Dedicated high-reliability file system for special monitoring
- ◆ Simplified Chinese, English, Persian, Russian, French, Spanish etc. over twenty languages
- ◆ A powerful mobile control and monitoring features to support Window Mobile, Symbian, Android, iPhone and Blackberry etc
- ◆ Support Multi-language OSD

Specifications

		EN-6604V	EN-6608V	
System	Main Processor	High performance embedded microprocessor		
	System Resource	Pentaplex: Live recording, Playback, Backup, Remote access, PTZ control, Mobile monitoring		
	Control Mode	Front panel, USB mouse, IR remote control, Keyboard, Network		
Video	Input	4×BNC,(1.0Vp-p,75Ω)	8×BNC,(1.0Vp-p,75Ω)	
	Standard	NTSC 120F/S;PAL100F/S		
	Output	1×BNC,(1.0Vp-p,75Ω),1×VGA		
Audio	Input	4×RCA		
	Output	1×BNC		
Display	Display Split	1/4	1/4/8	
	Resolution	VGA:1024*768, 800*600		
	Tour Display	Support		
Recording	OSD	Camera title, Time, Video loss, Motion detection, Recording		
	Video/Audio-compression Standard	H.264/ADPCM		
	Image Resolution	CIF(352*288/352*240)		
	Encoding stream	Main stream	Main stream: 30FPS/CH(CIF)	
		Extra	CIF: 1-5FPS/CH(CIF)	
	Recording Mode	Manual, schedule(regular continuous), MD(Video detection: <Motion detection, Video blank, video loss>, Alarm)Stop		
Recording Priority	Manual>Alarm>Motion detection			
Video detection & Alarm	Trigger events	Recording, PTZ movement, Alarm, E-mail		
	Motion detection	Zones:396 (22*18) ,Sensitivity:1-5 (Level 5 is the highest)		
	Video loss	Support		
	Alarm input/output	None		
Playback & Backup	Playback channel	4CH	8CH	
	Playback speed	CIF: 25FPS/CH		
	Search mode	Time/date, Alarm, Motion detection		
	Playback function	Playback function Play, Pause, Stop, Fast forward, Slow forward, Full screen etc. Recording files can be viewed by dragging the progress bar back and forth		
	Backup mode	U-disk/Hard disk/USB CD/DVD-RW/Download		
Network	Physical interface	RJ-45port(10/100M)		
	Network function	TCP/IP,UDP,DHCP,DNS,IP filter, PPPOE, E-mail, Alarm server, UPNP, DDNS,DNS Binding		
	Remote operation	Monitor, PTZ control, Playback, System setting, files download, Log information		
	Mobile monitoring	Support Window Mobile, Symbian, Android, iPhone, Blackberry etc.		
Hard Disk	Hard disk	1 SATA port, the capacity of single hard disk MAX 2T		
	Space occupation	Audio: 14.4MB/H, Video: 56-900MB/H		
	HDD management	Hard disk hibernation technology, HDD faulty alarm, file restoration		
Auxiliary Interface	USB	Two USB2.0 interface, for connecting mouse, U-disk, USB hard disk		
	RS485	PTZ control		
Environment	Power supply	12V/3A		
	Working environment	-10℃~+55℃/10~90%RH/86~106Kpa		
	Dimension	250*235*45mm(Product size)		

Design and specifications are subject to change without notice.

تأیید شده رسمی محصولات EBM.